On P vs NP

- GRAPH ISOMORPHISM is not known to be in $\mathbf{P}$ or $\mathbf{NP}$-complete.
- Are there problems in $\mathbf{NP}$ that are neither in $\mathbf{P}$ nor $\mathbf{NP}$-complete?

  Yes, at least if $\mathbf{P} \neq \mathbf{NP}$.

Theorem. If $\mathbf{P} \neq \mathbf{NP}$, then there is a language in $\mathbf{NP}$ which is neither in $\mathbf{P}$ nor $\mathbf{NP}$-complete.

Isomorphism and Density

- All known $\mathbf{NP}$-complete languages are *polynomially isomorphic.*
- Languages K, L are polynomially isomorphic if there is a function $h : \Sigma^* \mapsto \Sigma^*$ such that
  (i) h is bijection;
  (ii) for each $x \in \Sigma^*$, $x \in K$ iff $h(x) \in L$;
  (iii) h and h^{-1} are polynomial-time computable.
- A reduction is not necessarily a polynomial time isomorphism (not a bijection) but with a padding function a isomorphism is obtained.

- A function $pad : (\Sigma^*)^2 \mapsto \Sigma^*$ is a padding function for L if
  (i) pad is computable in logarithmic space;
  (ii) for each $x, y \in \Sigma^*$, $pad(x, y) \in L$ iff $x \in L$;
  (iii) for each $x, y \in \Sigma^*$, $|pad(x, y)| > |x| + |y|$;
  (iv) there is a logarithmic-space algorithm which given $pad(x, y)$ recovers y.

Example. A padding function for SAT:

Given x (a conjunction of m clauses with n variables), $pad(x, y)$ is all clauses of x together with $m + |y|$ new clauses and $|y| + 1$ more variables where the m new clauses are copies of the clause x_{n+1} and where the $m + i$th new clause is either $\neg x_{n+i+1}$ or x_{n+i+1} depending on whether the ith symbol in y is 0 or 1.

- If R is a reduction from K to L and pad is a padding function for L, $pad(R(x), x)$ is a length-increasing one-to-one reduction.

  Furthermore, there is a logarithmic-space algorithm for the inverse of $pad(R(x), x)$.
- If there is a reduction from K to L and a reduction from L to K and the reductions are length-increasing, one-to-one and logarithmic-space invertible, then K, L are polynomially isomorphic.
- Corollary: The following $\mathbf{NP}$-languages are polynomial isomorphic: SAT, HAMILTON PATH, CLIQUE, MAX CUT, TRIPARTITE MATCHING, KNAPSACK, ...

Density

Density of a language L:

$$\mathrm{dens}_L(n) = |\{x \in L : |x| \leq n\}|$$

Proposition. If $K, L \subseteq \Sigma^*$ are polynomially isomorphic, then dens_K and dens_L are polynomially related. ($\mathrm{dens}_L(n) \leq \mathrm{dens}_K(p(n))$)

- A *sparse* language: polynomially bounded density function
- A *dense* language: superpolynomial density function

- Examples:
  Any unary language ($\subseteq \{0\}^*$) is sparse.
  All **NP**-complete language seen this far are dense.

Theorem. If a unary language $U \subseteq \{0\}^*$ is **NP**-complete, then $\mathbf{P} = \mathbf{NP}$.

Theorem. If a sparse language is **NP**-complete, then $\mathbf{P} = \mathbf{NP}$.

ORACLES

- The idea: study complexity in a setting where a part of the computation comes "for free".
- Can be used for exploring conjectures (like $\mathbf{P} \stackrel{?}{=} \mathbf{NP}$) in an alternative setting.
- Can isolate orthogonal (independent) sources of complexity.

Definition.

- An oracle Turing machine $M^?$:
  query string, query state $q?$, answer states q_{YES}, q_{NO}
  (depending on whether for y on the query string $y \in A$ for the oracle set A).
  Computation of $M^?$ with oracle A on input x: $M^A(x)$.
- For any time complexity class $\mathcal{C}$ and oracle A there is a corresponding complexity class $\mathcal{C}^A$.

Theorem. There is an oracle A for which $\mathbf{P}^A = \mathbf{NP}^A$.

Proof: Let A be **PSPACE**-complete. Then

$$\mathbf{PSPACE} \subseteq \mathbf{P}^A \subseteq \mathbf{NP}^A \subseteq \mathbf{NPSPACE} \subseteq \mathbf{PSPACE}$$

Theorem. There is an oracle B for which $\mathbf{P}^B \neq \mathbf{NP}^B$.

Lessons to be learned w.r.t. $\mathbf{P} \stackrel{?}{=} \mathbf{NP}$

- By the above $\mathbf{P} \neq \mathbf{NP}$ is possible; non-trivial conjecture.
- "Ordinary proof techniques" are not sufficient for establishing $\mathbf{P} \stackrel{?}{=} \mathbf{NP}$.

  They are not affected by oracles.

Examples

- $\mathbf{P}^A \subseteq \mathbf{NP}^A$:

  can be shown as $\mathbf{P} \subseteq \mathbf{NP}$; ordinary proof technique.
- Given an oracle A, if $\mathbf{P}^A \neq \mathbf{NP}^A$, then there is a language in $\mathbf{NP}^A$ which is not in $\mathbf{P}^A$ nor $\mathbf{NP}^A$-complete

  The same proof as for the case without oracles works **except** that the proof uses SAT which is particular for $\mathbf{NP}$.

  What is SAT^A?

$$C^A = \{(M^A, x) : \text{ nondet. oracle machine } M^A \text{ accepts } x \text{ in time } |x| \}$$

Monotone Circuits

- **Conjecture B.** $\mathbf{NP}$-complete problems have no polynomial circuits, uniform or not.
- Lower bounds on the size of circuits for families of functions are hard to establish.
- Consider a weaker circuit model: monotone circuits (ones without NOT gates).
- Monotone circuits can only compute monotone functions: output cannot changed from $\mathbf{True}$ to $\mathbf{False}$ by changing input from $\mathbf{False}$ to $\mathbf{True}$.

- Some $\mathbf{NP}$-complete problems are monotonic, e.g., HAMILTON PATH and CLIQUE.
- How small can the monotone circuits coding these problems be?
- Let CLIQUE$_{n,k}$ be the Boolean function deciding whether a graph $G = (V, E)$ with n nodes has a clique of size k.

Theorem. (Razborov's Theorem): There is a constant c such that for large enough n all monotone circuits for CLIQUE$_{n,k}$ with $k = n^{1/4}$ have size at least $2^{cn^{1/8}}$.

- To show $\mathbf{P} \neq \mathbf{NP}$ it would be sufficient to establish that all monotone languages in $\mathbf{P}$ have polynomial monotone circuits.
- However, this does not hold.