From NFA to Boolean Circuits

The purpose of this exercise is to demonstrate the computational power and versatility of Boolean circuits.

Assume that we are given a non-deterministic finite state automaton (an NFA) $\mathcal{A}$ over the binary alphabet $\Sigma = \{0, 1\}$ and a fixed integer constant n. Our task is to construct a Boolean circuit with input gates $x_1, \ldots, x_n$ that has value 1 for a truth assignment $T : \{x_1, \ldots, x_n\} \to \{0, 1\}$ iff $\mathcal{A}$ accepts the string $T(x_1)T(x_2)\ldots T(x_n)$. (Note that we may use 1 for *true* and 0 for *false* in this exercise.)

Preliminary Notes

We will use Boolean circuits that are extensions to those described in Papadimitriou's book. An OR-gate with in-degree k, $\bigvee_{x \in \{a_1,\ldots,a_k\}} x$, is defined to be (i) an input gate with sort *false* if $k = 0$, (ii) the gate a_1 if $k = 1$ and (iii) for $k \geq 2$, the following sub-circuit of $k-1$ OR-gates with in-degree 2: $(\ldots(a_1 \vee a_2) \vee a_3) \vee \cdots \vee a_k)$. Thus our extensions do not expand the expressive power of Boolean circuits but are only used for the sake of convenience.

The Construction

Let the NFA be $\mathcal{A} = \langle Q, \Sigma, \Delta, \mathcal{F}, q_{init} \rangle$, where $Q = \{q_1, \ldots, q_k\}$ is the finite set of states, $\Sigma = \{0, 1\}$ is the binary alphabet, $\Delta \subseteq Q \times \Sigma \times Q$ is the (non-deterministic) transition relation, $\mathcal{F} \subseteq Q$ is the set of accepting states and $q_{init} \in Q$ is the initial state. A sequence $q'_0 \ldots q'_j$ of states is *legal* for input $x = x_1 x_2 \ldots x_n \in \Sigma^n$, $n \geq j$, iff $\langle q'_{i-1}, x_i, q'_i \rangle \in \Delta$ for all $1 \leq i \leq j$. $\mathcal{A}$ *accepts* $x = x_1 x_2 \ldots x_n \in \Sigma^n$ iff there is a legal sequence $q'_0 \ldots q'_n$ of states for x such that $q'_0 = q_{init}$ and $q'_n \in \mathcal{F}$.

The circuit $\mathcal{C} = \langle G, E \rangle$ is build as follows. The input gates of $\mathcal{C}$ consists of the following.

1. The gates $q_{1,0}, \ldots, q_{k,0}$ with the sorts (i) $s(q_{i,0}) = \mathit{true}$ if $q_i = q_{init}$, and (ii) $s(q_{i,0}) = \mathit{false}$ otherwise. These gates describe the initial state of the automaton.
2. The gates $x_1, \ldots, x_n$ with the sorts $s(x_i) = x_i$ for the input string.

The other gates are the gates $q_{i,j}$, where $1 \leq i \leq k$ and $1 \leq j \leq n$ and the necessary gates for the sub-circuits:

$$q_{i,j} := \bigvee_{\langle q_{i'}, 1, q_i \rangle \in \Delta} (q_{i',j-1} \wedge x_j) \vee \bigvee_{\langle q_{i'}, 0, q_i \rangle \in \Delta} (q_{i',j-1} \wedge \neg x_j).$$

Thus, a gate $q_{i,j}$, $j \geq 1$, evaluates to true iff $q_{i',j-1}$ is true and either (i) there is a transition from the state $q_{i'}$ to the state q_i with symbol 1 and the input string contains 1 in the position j, or (ii) there is a transition from the state $q_{i'}$ to the state q_i with symbol 0 and the input string contains 0 in the position j. Finally, the output gate o is defined by $o := \bigvee_{q_i \in \mathcal{F}} q_{i,n}$, the intuition being that o evaluates to true iff the automaton can be in an accepting state after reading the whole input. It is easy to show by induction that, given a truth assignment on the input gates $x_1, \ldots, x_n$ corresponding to the input string, the gate $q_{i,j}$ has the value *true* iff there is a legal sequence $q_{init} \ldots q_i \in Q^{j+1}$ of $j+1$ states leading to the state q_i on input $x_1 \ldots x_n$. The value of o is clearly *true* iff the corresponding string $x_1 \ldots x_n$ is accepted by $\mathcal{A}$.

As an example, consider the automaton shown on the left in Figure 1. A corresponding circuit for $n = 3$ is shown on the right hand side.



Figure 1: An NFA and a corresponding Boolean circuit for $n = 3$.

7.4.6

The Kleene star of a language L is $L^\star = \{x_1 \ldots x_k \mid k \geq 0 \text{ and } x_1, \ldots, x_k \in L\}$. Our goal is to show that $\mathbf{P}$ and $\mathbf{NP}$ are closed under the Kleene star. That is, if $L \in \mathbf{P}$, then $L^\star \in \mathbf{P}$. Similarly for $\mathbf{NP}$.

Suppose that $L \in \mathbf{NP}$, i.e., L is decided by a non-deterministic Turing machine M in polynomial time. Then $L^\star$ is decided by a non-deterministic Turing machine M' in polynomial time, as described in the following. Assume an input string x. If $x = \varepsilon$, then M' accepts. Otherwise, M' splits x non-deterministically into at most $|x|$ non-empty strings $x'_1, \ldots, x'_k$ such that $x'_1 \ldots x'_k = x$. Then M' runs M as a subroutine on each of the strings and accepts iff each subroutine run ended in a "**yes**"-state. It is obvious from the construction that $\mathcal{L}(M') = L^\star$ and that M' works in non-deterministic polynomial time. Thus **NP** is closed under Kleene star.

Suppose that $L \in \mathbf{P}$, i.e., L is decided by a deterministic Turing machine M in polynomial time. Now we cannot use the previous splitting approach since there are exponentially many, namely $\sum_{k=0}^{n-1} \binom{n-1}{k} = 2^{n-1}$, possible splittings for an input of length n. However, by using dynamic programming techniques, $L^\star$ is decided by the following algorithm, where $x^{i,j}$ means the substring of x from the ith position to the jth position. The idea is to keep already computed information in a Boolean array (of size polynomial in $|x|$) and use it instead of recomputing.

Input: a string $x = x_1 \ldots x_n$ and a machine M deciding L
Output: *true* iff $x \in L^\star$
Variables: a Boolean array *postfix_in_*$L^\star[n]$, initialized to *false*s

if $x = \varepsilon$ **then**
  return *true*;
for$(i = n; i \geq 1; i - -)\,\{$
  if $M(x^{i,n}) =$ **yes then**
    *postfix_in_*$L^\star[i] :=$ *true*;
  for$(j = i; j < n; j + +)\,\{$
    if $M(x^{i,j}) =$ **yes** $\wedge$ *postfix_in_*$L^\star[j+1] =$ *true* **then**
    *postfix_in_*$L^\star[i] :=$ *true*;
  $\}$
$\}$
if *postfix_in_*$L^\star[1] =$ *true* **then return**(**yes**); **else return**(**no**);

In the algorithm, an element *postfix_in_*$L^\star[i]$ is used to collect information on whether the postfix string $x^{i,n}$ belongs to the language $L^\star$. For a postfix string $x^{i,n}$, there are $n - i$ ways it can belong to the language $L^\star$: (i) $x^{i,n}$ belongs to L, or (ii) $x^{i,i}$ belongs to L and $x^{i+1,n}$ belongs to $L^\star$, or (iii) $x^{i,i+1}$ belongs to L and $x^{i+2,n}$ belongs to $L^\star$, and so on. The algorithm proceeds from the end of the input string, saving the results already computed in the array *postfix_in_*$L^\star$. The running time of the algorithm without the calls to the machine M is $\mathcal{O}(n^k)$ for some fixed $k \geq 2$ depending of the implementation of the programming language operations, e.g. how substrings are extracted from a string, — certainly these can be done in polynomial time. The algorithm makes $\frac{n(n+1)}{2}$ queries to the machine M deciding L, all of which are carried out in polynomial time. Thus $L^\star$ can be

decided in deterministic polynomial time and **P** is closed under Kleene star.

7.4.3 (a)

Definition 7.1 *Let $f : \mathbb{N}_+ \to \mathbb{N}_+$. f is a* proper complexity function *if*

1. *f is non-decreasing, i.e., $f(n+1) \geq f(n)$ for all $n \in \mathbb{N}_+$ and*
2. *there is a k-string Turing machine M_f with input and output such that, given an input of length n, M_f outputs $\sqcap^{f(n)}$ on its output string in time $\mathcal{O}(n + f(n))$ and uses $\mathcal{O}(f(n))$ space besides its input and output.*

Assume now that f and g are proper complexity functions, i.e., non-decreasing functions such that we have k_f- and k_g-string Turing machines M_f and M_g, respectively, calculating them and fulfilling the second condition in the above definition.

Case: $f + g$

Clearly the function $(f + g)(n) = f(n) + g(n)$ is non-decreasing if f and g are. Now, since we have M_f and M_g, we can construct a $k_f + k_g + 1$ -string Turing machine M_{f+g} fulfilling the requirements in the definition for proper complexity fuctions as follows. Given an input, M_{f+g} first runs M_f on the input and thus calculates the value $f(n)$ on the k_fth string. M_{f+g} then copies the input into the string $k_f + 1$ and then runs M_g on it, computing the value $g(n)$ on the string $k_f + k_g$. Finally, M_{f+g} concatenates the strings k_f and k_g on its output string $k_f + k_g + 1$. Clearly (i) the output string has the value $f(n)+g(n)$, (ii) the machine runs in time $\mathcal{O}(n + f(n) + n + g(n) + f(n) + g(n)) = \mathcal{O}(n + f(n) + g(n))$ and (iii) the maximum amount of space used by M_{f+g} is $\mathcal{O}(\max\{f(n), g(n)\})$ (the input and output strings are not counted in). Therefore $f + g$ is also a proper complexity function.

Case: $f \cdot g$

Clearly the function $(f \cdot g)(n) = f(n) \cdot g(n)$ is non-decreasing if f and g are. The construction for the machine $M_{f \cdot g}$ is similar to the machine M_{f+g} except that, in the last phase, the string k_f is copied into the string $k_f + k_g + 1$ k_g times. The time requirement now is $\mathcal{O}(n + f(n) + n + g(n) + f(n) \cdot g(n)) = \mathcal{O}(2n + (f(n) + 1) \cdot (g(n) + 1) - 2) = \mathcal{O}(2n + 2f(n) \cdot 2g(n) - 2) = \mathcal{O}(n + f(n) \cdot g(n))$ and the space consumption stays the same. Therefore $f \cdot g$ is also a proper compexity function if f and g are.

Case: 2^g

Clearly the function $2^g(n) = 2^{g(n)}$ is non-decreasing if g is. We define the machine M_{2^g} so that it first calculates the value $g(n)$ in unary on the string k_g and then, using auxiliary strings $k_g + 1$ and $k_g + 2$, does the following. First, M_{2^g} prints one $\sqcap$ symbol on the string $k_g + 2$. Then, using the string $k_g + 1$, it calculates in unary, how many symbols there are on the string $k_g + 2$ and then appends the same amount of new $\sqcap$ symbols on $k_g + 2$. M_{2^g} repeats this as many times as there are symbols on the string k_g, that is, $g(n)$ times. Therefore, at the end, the string $k_g + 2$ will have $2^{g(n)}$ $\sqcap$s. Finally, M_{2^g} copies the contest of the string $k_g + 2$ into its output string $k_g + 3$. The time consumption now is $\mathcal{O}(n + g(n) + 2^{g(n)}) = \mathcal{O}(n + 2^{g(n)})$ as required and the space consumption is clearly $\mathcal{O}(n + 2^{g(n)})$. Therefore 2^g is also a proper compexity function if g is.

Case: $f(g)$

Clearly the function $(f(g))(n) = f(g(n))$ is non-decreasing if f and g are. The (non-working) construction for the machine $M_{f(g)}$ is such that $M_{f(g)}$ first calculates the value $g(n)$ on the string k_g and then uses it as input to the machine M_f that calculates the value $f(g(n))$ into the output string $k_g + k_f$. This construction is *not* correct if f grows stricly lower than the linear function $f(n) = n$. To see why this is the case, consider functions $g(n) = 2^n$ and $f(n) = \log n$. Now $f(g(n)) = n$ but the machine $M_{f(g)}$ uses time and space proportional to 2^n. For functions f that grow at least as fast as the linear function, the construction clearly fulfills the requirements for a machine computing proper complexity functions. Fortunately, (i) the time complexity functions are in practise always at least linear since a machine must be able to read its input and (ii) the only sub-linear space complexity functions used in this course are (fixed powers of) log functions which, as we know, are proper. Therefore, the partial failure of this construction is not important for us.