RELATIONS BETWEEN COMPLEXITY CLASSES

- Basic requirements for complexity classes
- Complexity classes
- Hierarchy theorems
- Reachability method
- Class inclusions
- Simulating nondeterministic space
- Closure under complement

(C. Papadimitriou: *Computational complexity*, Chapter 7)

© 2006 TKK, Laboratory for Theoretical Computer Science

1. Basic Requirements for Complexity Classes

A complexity class is specified by

- model of computation (multi-string TMs)
- mode of computation (deterministic, nondeterministic,...)
- resource (time, space, ...)
- bound (function f)

A *complexity class* is the set of all *languages* decided by some multi-string Turing machine M operating in the appropriate mode, and such that, for any input x, M expends at most $f(|x|)$ units of the specified resource.

© 2006 TKK, Laboratory for Theoretical Computer Science

Reasonable bound functions

Definition. A function $f : \mathbf{N} \to \mathbf{N}$ is a *proper complexity function* if f is nondecreasing and there is a k-string TM M_f with input and output such that on any input x,

1. $M_f(x) = \sqcap^{f(|x|)}$ where $\sqcap$ is a *quasi-blank* symbol,
2. M_f halts after $\mathrm{O}(|x| + f(|x|))$ steps, and
3. M_f uses $\mathrm{O}(f(|x|))$ space besides its input.

- Examples of proper complexity functions $f(n)$:

  $$c,\ n,\ \lceil \log n \rceil,\ \log^2 n,\ n \log n,\ n^2,\ n^3 + 3n,\ 2^n,\ \sqrt{n},\ n!,\ \ldots$$

- If f and g are proper, so are, e.g., $f + g$, $f \cdot g$, 2^g.
- Only proper complexity functions will be used as bounds.

© 2006 TKK, Laboratory for Theoretical Computer Science

Precise Turing machines

Definition. Let M be a deterministic/nondeterministic multi-string Turing machine (with or without input and output).

Machine M is *precise* if there are functions f and g such that for every $n \geq 0$, for every input x of length n, and for every computation of M,

1. M halts after precisely $f(|x|)$ steps and
2. all of its strings (except those reserved for input and output whenever present) are at halting of length precisely $g(|x|)$.

(Precise bounds will be convenient in various simulation results).

© 2006 TKK, Laboratory for Theoretical Computer Science

Simulating TMs with precise TMs

Proposition. Let M be a deterministic or nondeterministic TM deciding a language L within time/space $f(n)$ where f is proper.

Then there is a precise TM M' which decides L in time/space $\mathrm{O}(f(n))$.

Proof sketch.

The simulating machine M'

1. computes a yardstick/alarm clock $\sqcap^{f(|x|)}$ using M_f and
2. simulates M for exactly $f(|x|)$ steps *or*
   simulates M using exactly $f(|x|)$ units of space.

© 2006 TKK, Laboratory for Theoretical Computer Science

2. Complexity Classes

- Given a proper complexity function f, we obtain following classes:

  $\mathbf{TIME}(f)$ (deterministic time)
  $\mathbf{NTIME}(f)$ (nondeterministic time)
  $\mathbf{SPACE}(f)$ (deterministic space)
  $\mathbf{NSPACE}(f)$ (nondeterministic space)

- The bound f can be a family of functions parameterized by a non-negative integer k; meaning the union of all individual classes.

  The most important are: $\mathbf{TIME}(n^k) = \bigcup_{j>0} \mathbf{TIME}(n^j)$
  $\mathbf{NTIME}(n^k) = \bigcup_{j>0} \mathbf{NTIME}(n^j)$

© 2006 TKK, Laboratory for Theoretical Computer Science

Variety of complexity classes

P	=	$\mathbf{TIME}(n^k)$
NP	=	$\mathbf{NTIME}(n^k)$
PSPACE	=	$\mathbf{SPACE}(n^k)$
NPSPACE	=	$\mathbf{NSPACE}(n^k)$
EXP	=	$\mathbf{TIME}(2^{n^k})$
L	=	$\mathbf{SPACE}(\log(n))$
NL	=	$\mathbf{NSPACE}(\log(n))$

The relationships of these classes will be studied in the sequel.

© 2006 TKK, Laboratory for Theoretical Computer Science

Complements of decision problems

- Given an alphabet Σ and a language $L \subseteq \Sigma^*$, the *complement* of L

$$\overline{L} = \Sigma^* - L.$$

- For a decision problem A, the answer for the complement "A COMPLEMENT" is "yes" iff the answer for A is "no".

Example. SAT COMPLEMENT: given a Boolean expression ϕ in CNF, is ϕ unsatisfiable?

Example. REACHABILITY COMPLEMENT: given a graph (V,E) and nodes $v,u \in V$, is it the case that there is no path from v to u?

© 2006 TKK, Laboratory for Theoretical Computer Science

Closure under Complement

- For any complexity class C, $\mathbf{co}C$ denotes the class
$$\{\overline{L} \mid L \in C\}.$$
- All deterministic time and space complexity classes are closed under complement. Hence, e.g., $\mathbf{P} = \mathbf{coP}$.
Proof. Exchange "yes" and "no" states of the deciding machine.
- The same holds for nondeterministic *space* complexity classes (to be shown in the sequel).
- An important open question: are nondeterministic *time* complexity classes closed under complement? For instance, $\mathbf{NP} = \mathbf{coNP}$?

© 2006 TKK, Laboratory for Theoretical Computer Science

3. Hierarchy Theorems

- We derive a quantitative hierarchy result:
with sufficiently greater time allocation, Turing machines are able to perform more complex computational tasks.
- For a proper complexity function $f(n) \geq n$, define
$$H_f = \{M;x \mid M \text{ accepts input } x \text{ after at most } f(|x|) \text{ steps}\}.$$
- Thus H_f is the time-bounded version of H, i.e. the language of the HALTING problem.

© 2006 TKK, Laboratory for Theoretical Computer Science

Upper bound for H_f

Lemma. $H_f \in \mathbf{TIME}((f(n))^3)$.

Proof sketch.

A 4-string machine U_f deciding H_f in time $f(n)^3$ is based on

(i) the universal Turing machine U,

(ii) the single-string simulator of a multi-string machine,

(iii) the linear speedup machine, and

(iv) the machine M_f computing the yardstick of length $f(n)$ where n is the length of the input x.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

The machine U_f operates as follows:

1. M_f computes the alarm clock $\sqcap^{f(|x|)}$ for M (string 4).
2. The description of M is copied on string 3 and string 2 initialized to encode the initial state s and string 1 the input $\triangleright x$.
3. Then U_f simulates M and advances the alarm clock. If U_f finds out that M accepts input x within $f(|x|)$ steps, then U_f accepts, but if the alarm clock expires, then U_f rejects.

Observations:

- Since M is simulated using a single string, each simulation step takes $\mathrm{O}(f(n)^2)$ time.
- The total running time is $\mathrm{O}(f(n)^3)$ for $f(|x|)$ steps.

© 2006 TKK, Laboratory for Theoretical Computer Science

Lower bound for H_f

Lemma. $H_f \notin \mathbf{TIME}(f(\lfloor \frac{n}{2} \rfloor))$

Proof sketch.

- Suppose there is a TM M_{H_f} that decides H_f in time $f(\lfloor \frac{n}{2} \rfloor)$.
- Consider $D_f(M)$: **if** $M_{H_f}(M;M) =$ "yes" **then** "no" **else** "yes".
  Thus D_f on input M runs in time $f(\lfloor \frac{2|M|+1}{2} \rfloor) = f(|M|)$.
- If $D_f(D_f) =$ "yes", then $M_{H_f}(D_f, D_f) =$ "no", hence, $D_f;D_f \notin H_f$ and D_f fails to accept input D_f within $f(|D_f|)$ steps, i.e. $D_f(D_f) =$ "no", a contradiction.
- Hence, $D_f(D_f) \neq$ "yes". Then $D_f(D_f) =$ "no" and $M_{H_f}(D_f, D_f) =$ "yes". Therefore, $D_f;D_f \in H_f$, and D_f accepts input D_f within $f(|D_f|)$ steps, i.e., $D_f(D_f) =$ "yes", a contradiction again.

© 2006 TKK, Laboratory for Theoretical Computer Science

The time hierarchy theorem

Theorem. If $f(n) \geq n$ is a proper complexity function, then the class $\mathbf{TIME}(f(n))$ is strictly contained within $\mathbf{TIME}((f(2n+1))^3)$.

- $\mathbf{TIME}(f(n)) \subseteq \mathbf{TIME}((f(2n+1))^3)$ as f is nondecreasing.
- By the first lemma: $H_{f(2n+1)} \in \mathbf{TIME}((f(2n+1))^3)$.
- By the second lemma:
  $H_{f(2n+1)} \notin \mathbf{TIME}(f(\lfloor \frac{2n+1}{2} \rfloor)) = \mathbf{TIME}(f(n))$.

Corollary. $\mathbf{P}$ is a *proper* subset of $\mathbf{EXP}$.

- Since $n^k = \mathrm{O}(2^n)$, we have $\mathbf{P} \subseteq \mathbf{TIME}(2^n) \subseteq \mathbf{EXP}$.
- It follows by the time hierarchy theorem that
  $\mathbf{TIME}(2^n) \subset \mathbf{TIME}((2^{2n+1})^3) \subseteq \mathbf{TIME}(2^{n^2}) \subseteq \mathbf{EXP}$.

© 2006 TKK, Laboratory for Theoretical Computer Science

The space hierarchy theorem

Theorem. If $f(n) \geq n$ is a proper complexity function, then the class $\mathbf{SPACE}(f(n))$ is a *proper* subset of $\mathbf{SPACE}(f(n)\log f(n))$.

However, counter-intuitive results are obtained if non-proper complexity functions are allowed.

Theorem. (The Gap Theorem).

There is a recursive function f from the nonnegative integers to the nonnegative integers such that $\mathbf{TIME}(f(n)) = \mathbf{TIME}(2^{f(n)})$.

Proof sketch.

The bound f can be defined so that no TM M computing on input x with $|x| = n$ halts after number of steps between $f(n)$ and $2^{f(n)}$.

© 2006 TKK, Laboratory for Theoretical Computer Science

4. Reachability Method

Theorem. Let $f(n)$ be a proper complexity function. Then

(a) $\mathbf{SPACE}(f(n)) \subseteq \mathbf{NSPACE}(f(n))$ and
$\mathbf{TIME}(f(n)) \subseteq \mathbf{NTIME}(f(n))$.

(b) $\mathbf{NTIME}(f(n)) \subseteq \mathbf{SPACE}(f(n))$.

(c) $\mathbf{NSPACE}(f(n)) \subseteq \mathbf{TIME}(c^{\log n + f(n)})$.

Proofs.

(a) A TM is a NTM, too.

(b) Simulation of all choices within space $f(n)$ (see below).

(c) Proof by reachability method (see below).

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof of NTIME$(f(n)) \subseteq$ SPACE$(f(n))$

- Let $L \in$ **NTIME**$(f(n))$. Hence there is a precise nondeterministic Turing machine N that decides L in time $f(n)$.
- Let d be the degree on nondeterminism (maximal number of possible moves for any state-symbol pair in Δ).
- Any computation of N is a $f(n)$-long sequence of nondeterministic choices (represented by integers $0,1,\ldots,d-1$).
- The simulating deterministic machine M considers all such sequences of choices and simulates N on each.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- With sequence $(c_1,c_2,\ldots,c_{f(n)})$ M simulates the actions that N would have taken had N taken choice c_i at step i.
- If a sequence leads N to halting with "yes", then M does, too. Otherwise it considers the next sequence. If all sequences are exhausted without accepting, then M rejects.
- There is an exponential number of simulations to be tried but they can be carried out in *space* $f(n)$ by carrying them out one-by-one, always erasing the previous simulation to reuse space.
- As $f(n)$ is proper, the first sequence $0^{f(n)}$ can be generated in space $f(n)$.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof of NSPACE$(f(n)) \subseteq$ TIME$(c^{\log n+f(n)})$

The *reachability method* is used to prove the claim.

- Consider a k-string *nondeterministic* TM M with input and output which decides a language L within space $f(n)$.
- We develop a deterministic method for simulating the nondeterministic computation of M on input x within time $c^{\log n+f(n)}$ where $n=|x|$ and c is a constant depending on M.
- The *configuration graph* $G(M,x)$ of M is used:
  nodes are all possible configurations of M and there is an edge between two nodes (configurations) C_1 and C_2 iff $C_1 \xrightarrow{M} C_2$.
- Now $x \in L$ iff there is a path from $C_0=(s,\triangleright,x,\triangleright,\varepsilon,\ldots,\triangleright,\varepsilon)$ to some configuration of the form $C=(\text{"yes"},\ldots)$ in $G(M,x)$.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- A configuration $(q,w_1,u_1,\ldots,w_k,u_k)$ is a complete "snapshot" of a computation.
- Since M is a machine with input and output *deciding* L:
  – the output string can be neglected,
  – for the input string, only the cursor position can change, and
  – for all other $k-2$ strings, the length is at most $f(n)$.
- A configuration can be represented as $(q,i,w_2,u_2,\ldots,w_{k-1},u_{k-1})$ where $1 \le i \le n$ gives the cursor position on the input string.
- How many possible configurations does M have? At most
  $|K|(n+1)(|\Sigma|^{f(n)})^{2(k-2)} \le |K|2n(|\Sigma|^{2(k-2)})^{f(n)} \le nc_1^{f(n)} \le c_1^{\log n+f(n)}$
  for some constant c_1 depending on M.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- Hence, deciding whether $x \in L$ holds can be done by solving a reachability problem for a graph with at most $c_1^{\log n + f(n)}$ nodes.
- The problem can be solved, say, with a quadratic algorithm in time $c_2 c_1^{2(\log n + f(n))} \leq c^{\log n + f(n)}$ with $c = c_2 c_1^2$.
- The graph $G(M,x)$ needs not to be represented explicitly (e.g., as an adjacency matrix) for the reachability algorithm.
- The existence of an edge from C to C' can be determined on the fly by examining C, C', and the input x.

© 2006 TKK, Laboratory for Theoretical Computer Science

5. Class Inclusions

Corollary. $\mathbf{L} \subseteq \mathbf{NL} \subseteq \mathbf{P} \subseteq \mathbf{NP} \subseteq \mathbf{PSPACE} \subseteq \mathbf{EXP}$.

Proof.

1. $\mathbf{L} = \mathbf{SPACE}(\log n) \subseteq \mathbf{NSPACE}(\log n) = \mathbf{NL}$ follows by (a).
2. $\mathbf{NL} = \mathbf{NSPACE}(\log n) \subseteq \mathbf{TIME}(c^{\log n + \log n}) = \mathbf{TIME}(n^{2 \log c}) \subseteq \mathbf{P}$ follows by (c).
3. By (a) $\mathbf{TIME}(n^k) \subseteq \mathbf{NTIME}(n^k)$ which implies $\mathbf{P} \subseteq \mathbf{NP}$.
4. By (b) $\mathbf{NTIME}(n^k) \subseteq \mathbf{SPACE}(n^k)$ which implies $\mathbf{NP} \subseteq \mathbf{PSPACE}$.
5. By (a) and (c) $\mathbf{SPACE}(n^k) \subseteq \mathbf{NSPACE}(n^k) \subseteq \mathbf{TIME}(c^{\log n + n^k}) \subseteq \mathbf{TIME}(2^{n^{k+c'}}) \subseteq \mathbf{EXP}$.

© 2006 TKK, Laboratory for Theoretical Computer Science

Which inclusions are proper?

Corollary. The class $\mathbf{L}$ is a proper subset of $\mathbf{PSPACE}$.

Proof. The space hierarchy theorem tells us $\mathbf{L} = \mathbf{SPACE}(\log(n)) \subset \mathbf{SPACE}(\log(n)\log(\log(n))) \subseteq \mathbf{SPACE}(n^2) \subseteq \mathbf{PSPACE}$. □

It is believed that *all* inclusions of the complexity classes in $\mathbf{L} \subseteq \mathbf{NL} \subseteq \mathbf{P} \subseteq \mathbf{NP} \subseteq \mathbf{PSPACE} \subseteq \mathbf{EXP}$ are proper.

However, we only know that

- at least one of the inclusions between $\mathbf{L}$ and $\mathbf{PSPACE}$ is proper (but don't know which) and
- at least one of the inclusions between $\mathbf{P}$ and $\mathbf{EXP}$ is proper (but don't know which).

© 2006 TKK, Laboratory for Theoretical Computer Science

6. Simulating Nondeterministic Space

- The question is how efficiently can we simulate nondeterministic space by deterministic space?
- It follows by the previous theorem that

  $$\mathbf{NSPACE}(f(n)) \subseteq \mathbf{TIME}(c^{\log n + f(n)}) \subseteq \mathbf{SPACE}(c^{\log n + f(n)}).$$

  But can we do better than this?
- *Yes*, in fact. Nondeterministic space can be simulated with quadratic deterministic space (using a theorem that follows).

© 2006 TKK, Laboratory for Theoretical Computer Science

Savitch's theorem

Theorem. REACHABILITY $\in \mathbf{SPACE}(\log^2 n)$.

Proof sketch.

- Given a graph G and nodes x, y and $i \geq 0$, define $PATH(x,y,i)$: there is a path from x to y of length at most 2^i.
- If G has n nodes, any simple path is at most n long and we can solve reachability in G if we can compute whether $PATH(x,y,\lceil \log n \rceil)$ holds for any given nodes x, y of G.
- This can be done using *middle-first search*.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- **function** $path(x,y,i)$ /* middle-first search */
  if $i = 0$ **then**
  if $x = y$ or there is an edge (x,y) in G **then** return "yes"
  else for all nodes z **do**
  if $path(x,z,i-1)$ and $path(z,y,i-1)$ **then** return "yes";
  return "no"
- Proof that $path(x,y,i)$ correctly determines $PATH(x,y,i)$:
  If $i = 0$, then clearly $path$ correctly determines $PATH(x,y,0)$.
  For $i > 0$, $path(x,y,i)$ returns "yes" iff there is a node z with $path(x,z,i-1)$ and $path(z,y,i-1)$ holding. By the inductive hypothesis there are paths from x to z and from z to y both at most 2^{i-1} long. Then there is a path from x to y at most 2^i long.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- The algorithm is started with $path(x,y,\lceil \log n \rceil)$.
- $O(\log^2 n)$ space bound can be achieved by handling recursion using a stack containing a triple (x,y,i) for each active recursive call.
  For each node z put $(x,z,i-1)$ into the stack and call $path(x,z,i-1)$. If this fails, erase $(x,z,i-1)$ and put $(x,z',i-1)$ for the next z' otherwise erase $(x,z,i-1)$ and put $(z,y,i-1)$.
- As there are at most $\log n$ recursive calls active with each taking at most $3\log n$ space, the $O(\log^2 n)$ space bound is achieved.

© 2006 TKK, Laboratory for Theoretical Computer Science

Corollary. For any proper complexity function $f(n) \geq \log n$,

$$\mathbf{NSPACE}(f(n)) \subseteq \mathbf{SPACE}((f(n))^2).$$

Proof.

- To simulate an $f(n)$-space bounded NTM M on input x, run the previous algorithm on the configuration graph $G(M,x)$.
- The edges of the graph $G(M,x)$ are determined on the fly by examining the input x.
- The configuration graph has at most $c_1^{\log n + f(n)} \leq c^{f(n)}$ nodes.
- By Savitch's theorem, the algorithm needs at most $(\log c^{f(n)})^2 = f(n)^2 \log^2 c = O(f(n)^2)$ space.

Corollary. $\mathbf{PSPACE} = \mathbf{NPSPACE}$.

☞ Nondeterminism is less powerful with respect to space than time.

© 2006 TKK, Laboratory for Theoretical Computer Science

7. Closure under Complement

- A key result about reachability will be established:
  the number of nodes reachable from a node x can be computed in nondeterministic $\log n$ space!
- The complement (the number of nodes not reachable from x) can be handled in nondeterministic $\log n$ space, too!
  (This quantity can be obtained by a simple subtraction.)
- It is open (and doubtful) whether nondeterministic *time* complexity classes are closed under complement.

© 2006 TKK, Laboratory for Theoretical Computer Science

Functions computed by NTMs

When does a NTM M compute a function F from strings to strings?

- On input x, each computation of M either
  – outputs the correct answer $F(x)$ or
  – enters the rejecting "no" state.
- At least one computation must end up with $F(x)$ which must be unique for all such computations.
- Such a machine observes a space bound $f(n)$ iff for any input x, at halting all strings (except the ones reserved for input and output) are of length at most $f(|x|)$.

© 2006 TKK, Laboratory for Theoretical Computer Science

Immerman-Szelepscényi theorem

Theorem. Given a graph G and a node x, the number of nodes reachable from x in G can be computed by a NTM within space $\log n$.

Proof.

- Let us define $S(k)$ as the set of nodes in G which are reachable from x via paths of length k or less.
- The strategy is to compute values $|S(1)|, |S(2)|, \ldots, |S(n-1)|$ iteratively and recursively, i.e. $|S(i)|$ is computed from $|S(i-1)|$.
- Given that the number of nodes in G is n, the number of nodes reachable from x in G is $|S(n-1)|$.
- Let $G(v,u)$ mean that $v = u$ or there is an arc from v to u in G.

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

The nondeterministic algorithm:

$|S(0)| := 1;$
for $k := 1,2,...,n-1$ **do**
  $l := 0;$
  for each node $u := 1,2,...,n$ **do**
    check whether $u \in S(k)$ and set *reply* accordingly;
    /* See below how this is implemented */
    if $reply = true$ **then** $l := l + 1;$
  end for;
  $|S(k)| := l$
end for

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof–cont'd.

/* Check whether $u \in S(k)$ and set *reply* */
$m := 0$; $reply := false$;
for each node $v := 1,2,...,n$ **do**
  /* check whether $v \in S(k-1)$ */
  $w_0 := x$; $path := true$
  for $p := 1,2,...,k-1$ **do**
    guess a node w_p; **if** not $G(w_{p-1},w_p)$ **then** $path := false$
  end for
  if $path = true$ and $w_{k-1} = v$ **then**
    $m := m+1$; /* $v \in S(k-1)$ holds */
    if $G(v,u)$ **then** $reply := true$
  end if
end for
if $m < |S(k-1)|$ **then** "give up" (end in "no" state)

© 2006 TKK, Laboratory for Theoretical Computer Science

Proof—cont'd.

- Note that only $\log n$-space is needed as there are only nine variables: $|S(k)|,k,l,u,m,v,p,w_p,w_{p-1}$
  which each (an integer) can be stored in $\log n$ space.
- The algorithm computes correctly $|S(k)|$ (by induction on k):
  – If $k = 0$, then $|S(k)| = 1$ as given by the algorithm.
  – For $k > 0$, consider a computation that does not "give up". We need to show that counter l is incremented iff $u \in S(k)$.
  If counter l is incremented, then $reply = true$ implying that $u \in S(k)$, i.e. there is a path $(x =)w_0,\ldots,w_{k-1}(= v),u$.
  If $u \in S(k)$, then there is some $v \in S(k-1)$ such that $G(v,u)$. But as the computation does not "give up", $m = |S(k-1)|$ (which is the correct value by induction) and therefore all $v \in S(k-1)$ are verified as such and, thus, *reply* is set to *true*.
  – Moreover, clearly there is at least one accepting computation where paths to the members of $S(k-1)$ are correctly guessed.

© 2006 TKK, Laboratory for Theoretical Computer Science

Closure under Complement

Corollary. If $f(n) \geq \log n$ is a proper complexity function, then $\mathbf{NSPACE}(f(n)) = \mathbf{coNSPACE}(f(n))$.

Proof sketch.

- Suppose $L \in \mathbf{NSPACE}(f(n))$ is decided by an $f(n)$-space bounded NTM M. We build an $f(n)$-space bounded NTM $\overline{M}$ deciding $\overline{L}$.
- On input x, $\overline{M}$ runs the previous algorithm on the configuration graph $G(M,x)$ associated with M and x.
- $\overline{M}$ rejects if it finds an accepting configuration in any $S(k)$.
- Since $G(M,x)$ has at most $n_g = c^{f(n)}$ nodes, then $\overline{M}$ can accept if $|S(n_g - 1)|$ is computed without an accepting configuration.
- Due to bound n_g, $\overline{M}$ needs at most $\log c^{f(n)} = \mathrm{O}(f(n))$ space.

© 2006 TKK, Laboratory for Theoretical Computer Science

Learning Objectives

- The definitions and background of major complexity classes: **P**, **NP**, **PSPACE**, **NPSPACE**, **EXP**, **L**, and **NL**.
- The knowledge of basic relationships between complexity classes (inclusions and proper inclusions).
- Savitch's theorem and Immerman-Szelepscényi theorem.

© 2006 TKK, Laboratory for Theoretical Computer Science